## Site Plan Project Data Table Examples:

## Example 1: PROJECT DATA TABLE (RT-8 Zone)

	Permitted/	
Development Standard	Required	Proposed
Min. Tract Area (s.f.):	20,000	354,578
Maximum Density of Development (d.u./ac.)	8	7.25
Number of Dwelling Units <sup>1</sup>	64	59
MPDU	8 (12.5%)	8
Minimum Building Setbacks (ft.)		
from detached homes	30	52
from the street	25	25
from adjoining lots		
rear	20	20
side	10	10
Minimum Building Coverage (%):	40 <sup>1</sup>	17.5
Minimum Green Area (%)	45 <sup>1</sup>	47
Maximum Building Height (ft.):	35	35 (As measured from)
Parking Spaces	118	125

<sup>1</sup> Development including MPDU and TDRs

## Example 2: PROJECT DATA TABLE

PROJECT DATA TABLE				
	Permitted/			
Development Standard	Required	Proposed		
TDR Zone				
Development Method		Optional		
Min. Area of Development (ac.):		3.47		
Dwelling Units:				
One-family detached		9		
Min. Lot Area (sq. ft.):	9,000	9,000		
Min. Lot Width at FBL (ft.):	75	75		
Setback from the street (ft):	30	30		
Rear Yard (ft.):	25	25		
Side Yard (ft.):	8/25	8/25		
Lot Coverage (%):	30	30		
Building Height (ft.):	35	35		
RNC Zone				
Development Method		Optional		
Min. Area of Development (ac.):	10	46.82		
Density (dwelling/acre):	1	0.45		
Dwelling Units:	46	21		
One-family detached				
Min. Lot Area (sq. ft.):	4,000	13,670		
Setback from the street (ft.):	15	15		
Rear Yard (ft.):	-	20		
Side Yard (ft.):	8 <sup>1</sup>	8		
Lot Width (ft.):	25	25		
Rural Open Space (%):	65 – 85	76.6		
		(35.88 ac.)		
Common Open Space (ac.):		.76		
Lot Coverage (%):	35	35		
Building Height (ft.):	35	35		
Park Land Dedication (ac.):		1.2		

<sup>1</sup> But no less than that required for the abutting lot, which is not developed under the optional method.